

Huebsch is the answer.



OPL
18-100 lb Softmount
Washer-Extractors



18-100 lb Softmount Washer-Extractor Specifications

Models	HX18	HX25	HX35	HX55	HX75	HX100	
Capacity - lb (kg)	18 (8.2)	25 (11.3)	35 (15.9)	55 (24.9)	75 (34)	100 (45.4)	
Width - in (mm)	26" (660)	26" (660)	30 11/16" (780)	35 7/16" (900)	41 3/4" (1060)	47 1/4 (1200)	
Depth - in (mm)	31 5/16" (796)	35 1/4" (896)	39 1/4" (998)	49 3/4" (1010)	45 1/8" (1147)	52 9/16 (1335)	
Height - in (mm)	39 13/16" (1011)	39 13/16" (1011)	46 1/4" (1175)	59 1/16" (1500)	60" (1530)	75 9/16 (1920)	
Cylinder Diameter - in (mm)	20 7/8" (530)	20 7/8" (530)	25 9/16" (650)	29 1/2" (750)	33 7/16" (850)	38 9/16 (980)	
Cylinder Depth - in (mm)	13" (330)	17 5/16" (440)	19 3/4" (500)	20 7/8" (530)	21 1/8" (537)	23 1/2" (597)	
Cylinder Volume - cu. ft. (liters)	2.68 (76)	3.35 (95)	5.83 (165)	8.26 (234)	10.74 (304)	16.07 (570)	
Door Opening Size - in (mm)	11 13/16" (300)	11 13/16" (300)	11 13/16" (300)	15 3/4" (400)	15 3/4" (400)	19 11/16 (500)	
Wash Speed - RPM	10-50	10-50	10-50	10-50	10-50	10-50	
Distribution Speed - RPM	85	85	85	85	85	85	
Extract Speed - RPM	500-1000	500-1000	250-1000	250-1000	250-1000	500-800	
Extract G-Force	296	296	380	419	475	350	
Water Inlet Connection - in (mm)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	
Steam Inlet Connection - in (mm)	3/8" (10)	3/8" (10)	N/A	N/A	N/A	N/A	
Drain Diameter - in (mm)	2" (50)	2" (50)	2" (50)	3" (75)	3" (75)	3" (75)	
Motor Size - hp (kw)	1 (.75)	1 (.75)	2 (1.5)	4 (3)	5 (4)	7 (5.5)	
Voltage/Hz/	X 200-240/50-60/1-3	10	10	15	15	N/A	N/A
# of Wires/	Q 200-240/50-60/3	10	10	60	60	20	25
Phase/Circuit	P 380-415/50-60/3	10	10	15	20	15	20
Breaker - FLA	N 440-480/50-60/3	10	10	15	20	15	20
Shipping Dimensions Approx. - in (mm)	Width	28 3/4" (730)	28 3/4" (730)	33 7/16" (850)	38 3/16" (970)	44 1/8" (1120)	47 1/4 (1200)
	Depth	33 1/16" (840)	33 1/16" (840)	37 3/8" (950)	43 5/16" (1100)	49 5/8" (1260)	52 9/16 (1335)
	Height	46 1/16" (1170)	46 1/16" (1170)	59 1/16 (1500)	66 15/16" (1700)	68 1/2" (1740)	75 9/16" (1920)
Net Weight - lb (kg)	481 (218)	525 (238)	800 (363)	1177 (534)	1612 (731)	3351 (1520)	
Shipping Weight - lb (kg)	514 (233)	564 (256)	844 (383)	1287 (584)	1722 (781)	3741 (1697)	
Agency Approvals	cETL _{US} , CE	cETL _{US} , CE	cETL _{US} , CE	cETL _{US} , CE	cETL _{US} , CE	cETL _{US} , CE	

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

Printed in the U.S.A. ©Copyright 2009 Alliance Laundry Systems LLC

Flexibility

How do Huebsch softmount units deliver flexibility and results to my operation?

Versatile control.

With Huebsch's versatile programmable micro-processor control, laundries have 39 pre-programmed cycles and room for 99 total programs. Temperature-controlled fills and a thermal cool-down aid chemical performance, producing excellent finished results no matter what type of linen is being washed.

Variable speed performance.

Programmable wash speeds also ensure superior linen care, while high-speed extracts of up to 475 G-Force on some models reduce drying times significantly.

The right sizes.

Huebsch softmount washer-extractors come in a range of capacities, including 18, 25, 35, 55, 75 and 100 lbs, meaning there's a size to fit the needs of any size laundry.

Easy to install.

Because of their heavy-duty suspension systems, Huebsch softmounts don't require any special foundations. That keeps installation costs low and offers flexibility in where they can be placed.



Alliance Laundry Systems, Shepard Street, Ripon, WI 54971 Telephone: 1-800-553-5120