

Huebsch is the answer.



OPL
Galaxy 400, 200
Washer-Extractors





Huebsch is the answer.

Anybody can sell you laundry equipment and discuss the merits of each nut and bolt. However, at Huebsch, our priority is answering your questions about how working with us will make your business easier to run and more profitable.

Customers have selected Huebsch products for their ease of use, supreme durability and because owning a Huebsch product brings a service and support network that's unmatched within the industry. For profitability, reliability and ease of use, Huebsch is the answer.

Quality You Can Touch

I need a machine that's durable and works. What do Huebsch Galaxy 400 and 200 washer-extractors bring to the table?

Heavy-duty design.

The foundation of Huebsch washer-extractors' durability is the all-welded structural steel frame. Compared to lighter weight, riveted designs of the competition, Huebsch frames set the standard for extreme durability.

Convenient chemical dispensing.

Our fill-and-forget dispenser lets staff add all chemicals — four in total — at the start of the cycle. That means your laundry workers can be more productive. Huebsch washer-



extractors also are designed for automatic supply injection systems for greater convenience.

Open, shut and lock with ease.

Our new ergonomically friendly door handles close easily and lock reliably. No more wasted time due to door lock error codes. Huebsch keeps your laundry running at maximum productivity.



Advanced protection where you need it.

Bearing replacement is one of the most expensive repairs to your washer-extractor. Huebsch's triple-lip seals and stainless steel shaft deliver the strongest line of defense in protecting bearings from the damaging effects of moisture long after the warranty period.

Keeping it Green

What makes this Huebsch machine green to save my operation some green?

Multiple water levels deliver major savings.

With the Galaxy 400 control, Huebsch gives you the power to set water levels to conserve this precious (and often expensive) resource. While many competing models offer just three water levels to choose from, we give you 30. Savings can be as great as 55% compared to older fixed-cycle models. The Galaxy 200 control offers high and low water selections.



Advanced leak detection eliminates wasted water.

We've answered laundry managers' calls to help eliminate the issue of stuck drain valves with our advanced leak detection. Both the Galaxy 400 and 200 models feature a display indicator to let you know if a valve is stuck. No more wasted resources ... or money.

High-speed extraction reduces drying time.

At 100 G-Force, the Galaxy 400 washer-extractor removes more water — as much as a ½ gallon in a 30 lb washer — than many competing models. That means reduced drying time and lower gas consumption for your laundry ... did we mention improved throughput? Huebsch Galaxy 200 models produce extracts of 85 G-Force.

Control Your Costs

How does the Galaxy 400 control increase my profitability?

Infrared communication means fast and easy changes to programs.

Managers with the Galaxy 400 control can easily program and retrieve operations data about



their machines through a PDA or laptop PC. Simple access to data and easy programming helps save time and ensures proper wash programs are being followed.



Galaxy 400 (G400)



Galaxy 200 (G200)

Unmatched Durability

Commercial laundry equipment is no small expense; I want peace of mind my equipment will last well into the future. What sets Huebsch apart from other brands in terms of reliability?

Not just standing behind our equipment, but standing beside you and your business.

Our made-in-America product comes with an industry-leading bond. We warranty the frame, cylinder, shaft, bearings and seals for five years. The entire machine receives Huebsch's standard three-year warranty. In addition, Huebsch has more service representatives in the field than most brands have in their whole organization. Huebsch support is further bolstered by an online component and a help line that takes 10,000 calls per year.



*Parts only, labor not included. See Huebsch Warranty Bond for specifics.

20-80 lb G400/G200 OPL Washer-Extractor Specifications

Models	HCN020		HCN030		HCN040		HCN060		HCN080		
Control Options	Galaxy 400, Galaxy 200		Galaxy 400, Galaxy 200		Galaxy 400, Galaxy 200		Galaxy 400, Galaxy 200		Galaxy 400, Galaxy 200		
Capacity - lb (kg)	20 (9)		30 (13.6)		40 (18)		60 (27)		80 (36)		
Overall Width - in (mm)	26" (660)		29" (737)		30 5/8" (778)		34 1/16" (865)		41 1/2" (1054)		
*Overall Depth - in (mm)	30 1/4" (767)		34 9/16" (878)		39 3/4" (1009)		42 9/16" (1081)		51 1/2" (1308)		
Overall Height - in (mm)	42" (1067)		45" (1142)		47 1/4" (1199)		49 7/8" (1267)		56 3/16" (1426)		
Cylinder Diameter - in (mm)	21" (533)		24" (610)		26 1/4" (667)		30" (762)		36" (916)		
Cylinder Depth - in (mm)	13 3/4" (349)		16" (406)		20 1/4" (514)		22" (559)		22" (559)		
Cylinder Volume - cu. ft. (liters)	2.76 (78.1)		4.19 (118)		6.34 (180)		9.0 (255)		12.4 (354)		
Door Opening Size - in (mm)	11 5/8" (295)		14 5/16" (364)		16 1/4" (413)		16 1/4" (413)		18 1/2" (470)		
Door Bottom To Floor - in (mm)	14 3/8" (365)		14" (356)		14 1/2" (368)		14 15/16" (379)		17 15/16" (455)		
Water Inlet Connection - in (mm)	2 @ 3/4" (19)		2 @ 3/4" (19)		2 @ 3/4" (19)		2 @ 3/4" (19)		2 @ 3/4" (19)		
Steam Inlet - in (mm)	N/A		N/A		1 @ 1/2" (13)		1 @ 1/2" (13)		1 @ 1/2" (13)		
Drain Diameter - in (mm)	1 @ 2" (52)		1 @ 2" (52)		1 @ 3" (76)		1 @ 3" (76)		1 @ 3" (76)		
Drain Height To Floor - in (mm)	4 1/2" (114)		4 1/2" (114)		4 13/16" (122)		4 11/16" (119)		5 3/4" (145)		
		2 Speed	F Speed	2 Speed	F Speed	2 Speed	F Speed	2 Speed	F Speed	F Speed	
Motor Size - hp (kw)	Wash	.15 (.11)	N/A	.24 (.18)	N/A	.4 (.3)	N/A	.55 (.41)	N/A	N/A	
	High Extract	.74 (.55)	1 (.75)	1.34 (1)	1 (.75)	1.8 (1.3)	2 (1.7)	2.7 (2.01)	3 (2.2)	5 (3.7)	
Total # of Speeds		2	6	2	6	2	6	2	6	6	
Cylinder Speeds - RPM (G Force)	Gentle	N/A	29 (.25)	N/A	27 (.25)	N/A	26 (.25)	N/A	24 (.25)	22 (.25)	
	Wash	55 (.9)	52 (.8)	49 (.8)	48 (.8)	51 (1)	46 (.8)	47 (.9)	43 (.8)	40 (.8)	
	Distribution	N/A	92 (2.5)	N/A	86 (2.5)	N/A	82 (2.5)	N/A	77 (2.5)	70 (2.5)	
	Very Low	N/A	366 (40)	N/A	343 (40)	N/A	328 (40)	N/A	307 (40)	280 (40)	
	Low	519 (80)	518 (80)	468 (75)	485 (80)	486 (88)	464 (80)	450 (86)	434 (80)	396 (80)	
	Medium	N/A	580 (100)	N/A	542 (100)	N/A	518 (100)	N/A	485 (100)	443 (100)	
***Voltage/Hz/ # of Wires/ Phase/ Circuit Breaker - FLA	B	120/60/2/1	20-16	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	C	380-415/50/4/3	15-4	N/A	15-4	N/A	15-5	N/A	15-5	N/A	
	F	440-480/60/3/3	15-4	N/A	15-4	N/A	15-5	N/A	15-5	N/A	
	O	220-240/60/3/3	15-5	N/A	15-7	N/A	20-7	N/A	20-10	N/A	
- FLA	Q	200-208/220-240/50/60/3/3	N/A	15-5	N/A	15-5	N/A	15-6	N/A	15-8	
	R	380-415/440-480/50/60/3/3	N/A	15-4	N/A	15-4	N/A	15-5	N/A	15-6	
	X	200-208/220-240/50/60/3/1/3	N/A	15-6	N/A	15-7	N/A	15-10	N/A	15-11	
	Y	208/220-240/60/2/3/1	15-8	N/A	20-10	N/A	30-14	N/A	N/A	N/A	
Shipping Dimensions Approx. - in (mm)	Width	29 1/2" (749)		32 1/2" (828)		34 1/4" (867)		38" (965)		48" (1219)	
	Depth	34 5/8" (879)		39 13/16" (1014)		44 5/8" (1133)		49" (1245)		56" (1422)	
	Height	51 1/2" (1308)		54 1/2" (1389)		56 3/4" (1441)		59" (1508)		65 3/4" (1670)	
Net Weight - lb (kg)	387 (176)		489 (222)		692 (314)		812 (368)		1374 (623)		
Shipping Weight - lb (kg)	420 (191)		530 (240)		734 (333)		854 (387)		1461 (663)		
Export Shipping Weight - lb (kg)	475 (215)		593 (269)		816 (370)		948 (430)		1573 (714)		
****Agency Approvals	cETLus, CE		cETLus, CE		cETLus, CE		cETLus, CE		cETLus, CE		

* Overall depth includes vacuum breaker to door handle.

** High & Very High Spin Speeds are available on the V Speed models only.

*** Circuit breaker and amp draw data shown are for models without electric heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines.

**** Agency approvals may vary depending on configuration. Consult factory for details. Steam connection requires 1/2" N.P.T.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

Printed in the U.S.A.

©Copyright 2009 Alliance Laundry Systems LLC



Alliance Laundry Systems, Shepard Street, Ripon, WI 54971 Telephone: 1-800-553-5120